

Product Specification Hide flooring

CE EN 14041: 2004

Inflammability	EN 13501-1	Cfl-S1
Slip resistance	DS R9	
Formaldehyde Group	ENV 717-1	E1

Product information

European classification EN 651



Total thickness	EN 428	ca. 2,00 mm
Wearlayer	EN 429	ca. 0,55mm
Wearlayer treatment	Super Guard	Super Guard
Total weight	EN 430	ca. 2600 g/m ²
Width	EN 426	2/4 m
Standard Length	EN 426	ca. 25 m
Weight of standard roll	130kg	ca. 260kg

Warranty

Residential use
15 years

Commercial use
5 years

Manufactured according
to the itec contract
floor standard

Technical information

Inflammability	EN 13501-1	Cfl-S1
Heat insulation	DIN 52612	0,05 m ² K/W
Dimensional stability	EN 434	0,10 %
Light fastness	DIN 53389	Class 6/7
Underfloor heating	DIN 52612	Suitable
Resistance to household chemicals	-	Very good
Hot welding	-	Suitable
Underfloor heating	ISO 8302	0,0108 m ² .K/W
Castor chair resistance	EN 425	very good
Antistatic	EN 1815	≤ 2 kV
Furniture leg resistance	EN 424	very good
Curling	EN 434	≤ 1mm (min ≤ 8mm required)
Dimensional stability	EN 434	≤ 0,1% (min ≤ 0,4% required)
Indentation	EN 434	≤ 0,1mm