



## Product Specification Copenhagen Flooring

### Technical Specification

Manufacturing Process	Flat Woven
Pile Content	Polyamide (100% PA 6.6 Ascend Ultron®)
Backing Content	100% recycled PET
Total Weight	1.75 g/m <sup>2</sup>   2.2 g/m <sup>2</sup>
Total Height	3.5mm   4mm
Width	400cm

### Performance

Wear Rating	Class 33 Commercial – Heavy
Castor Chair Test	EN985 test, Commercial (31 32 33) 25 000 cycles
Stroll Test	ISO 6356 <2kV
Thermal Conductivity	0.06 m <sup>2</sup> K/W
Flammability	Cfl-s1
Impact Sound Reduction	14dB   16dB
Luxury Class Rating	LC1

### Suitability

Inside Only  
Underfloor Heating  
UV Stable

### Recommended Adhesives

F Ball and Co	Styccobond F3, F40, F60, F66 <a href="http://www.f-ball.co.uk">www.f-ball.co.uk</a>
---------------	--

### General

Recommended Maintenance	Vacuum Daily. Do not over wet the areas. Professional cleaning is recommended periodically when the flooring becomes soiled. See website for full cleaning instructions.
Laying Instructions - Rolls	The Copenhagen range can be fully adhered to the floor, using a double stick method. See website for full fitting instructions.