



Product Specification

New England CONTRACT Flooring

Technical Specification

| | |
|-----------------------|-------------------------|
| Manufacturing Process | Flat Woven |
| Pile Content | Polypropylene |
| Total Weight | 1.635 gr/m ² |
| Total Height | 5.4mm |
| Width | 400cm |

Performance

| | |
|----------------------------|--|
| Wear Rating | Class 33 Commercial – Heavy |
| Castor Chair Test | EN 1307 (2014) + A1 (2016) 25,000 cycles |
| Antistatic | EN 14041:2008-05 |
| Thermal Conductivity | 0.045 (W/mK) |
| Fire Resistance | EN 13501-1 CFL-s1 if glued |
| Slip Resistance | DS |
| Luxury Class Rating | LC1 |
| Sound Insulation | 18dB |
| Colour Fastness Properties | Light 7, Water 4-5 |

Suitability

| | |
|------------------|--------------------|
| | Inside and outside |
| | Underfloor Heating |
| | UV Stable |
| TOG Rating | 1.2 |
| Bleach Cleanable | Dilute to 10% |

Recommended Adhesives

Internal

| | |
|-------------|---|
| F Ball & Co | Styccobond F3 Styccobond F60 www.f-ball.co.uk |
|-------------|---|

External

| | |
|-------------|---|
| F Ball & Co | Styccobond F73 PLUS Styccobond F74 Styccobond F81 www.f-ball.co.uk |
|-------------|---|

General

Recommended Maintenance

Vacuum Daily. Do not over wet the areas. Professional cleaning is recommended periodically when the flooring becomes soiled.

See website for full cleaning instructions.

Laying Instructions - Rolls

The Copenhagen range can be fully adhered to the floor, using a double stick method.

See website for full fitting instructions.