



Product Specification

New England CONTRACT Flooring

Technical Specification

Manufacturing Process	Flat Woven
Pile Content	Polypropylene
Total Weight	1.635 gr/m2
Total Height	5.4mm
Width	400cm

Performance

Wear Rating	Class 33 Commercial – Heavy
Castor Chair Test	EN 1307 (2014) + A1 (2016) 25,000 cycles
Antistatic	EN 14041:2008-05
Thermal Conductivity	0.045 (W/mK)
Fire Resistance	EN 13501-1 CFL-s1 if glued
Slip Resistance	DS
Luxury Class Rating	LC1
Sound Insulation	18dB
Colour Fastness Properties	Light 7, Water 4-5

Suitability

	Inside and outside
	Underfloor Heating
	UV Stable
TOG Rating	1.2
Bleach Cleanable	Dilute to 10%

Recommended Adhesives

Internal

F Ball & Co	Styccobond F3 Styccobond F60 www.f-ball.co.uk
-------------	---

External

F Ball & Co	Styccobond F73 PLUS Styccobond F74 Styccobond F81 www.f-ball.co.uk
-------------	---

General

Recommended Maintenance

Vacuum Daily. Do not over wet the areas. Professional cleaning is recommended periodically when the flooring becomes soiled.
See website for full cleaning instructions.

Laying Instructions - Rolls

The New England CONTRACT range can be fully adhered to the floor, using a double stick method.
See website for full fitting instructions.