
Product Specification

New York Flooring

Technical Specification

Manufacturing Process	Flat Woven
Pile Content	Polypropylene
Backing Content	Recycled Polyester Felt
Total Weight	ca. 2.000 gr/m ²
Total Height	ca. 4.5mm – 5.5mm
Width	400cm (and 500cm in limited colours)

Performance

Wear Rating	Class 23/32 (500cm) Class 23/33 (400cm) ISO 10361:2015 Method B / EN 1963:20017 TEST A (EN 1307:2014+A1:2016.)
Castor Chair Test	EN985:2001 pass >25000 cycles (EN 1307:2014+A1:2016.)
Stroll test	ISO 6356 <2kv
Thermal Conductivity	0.9 – 0.11m ² k/w
Flammability	Efl EN 13501-1 and BS 4740
Impact Sound Reduction	22 – 25dB
Luxury Rating Class	LC1

Suitability

	Inside only UV Stable Underfloor Heating
Bleach Cleanable	Dilute to 10%

Recommended Adhesives

F Ball & Co	Styccobond F3, F60, F66 www.f-ball.co.uk
Uzin Ltd	2428 www.uzin.co.uk
Mapei	Ultrabond Eco Fix PS

Please contact the adhesive company for more information.

General

Recommended Maintenance:	Vacuum daily. Bleach Cleanable for spot cleaning (dilute to 10%). Do not over wet the area. Professional cleaning is recommended periodically when the flooring becomes soiled. See website for full cleaning instructions.
Laying Instructions:	The New York Range can be installed by stretch fit or double stick methods. See website for full fitting instructions.