



Product Specification

Unnatural Flooring

Technical Specification

Product Definition	Woven Vinyl
Material	97% vinyl, 2% polyester, 1% glass fibre
Total Weight Tiles	4000 gr/m ² ±5%
Total Weight Rolls	3000 gr/m ² ±5%
Thickness Tiles	3.5mm
Thickness Rolls	3 mm
Sizes Tiles	50cm x 50cm
Sizes Rolls	50m x 2m

Performance

Wear Classification	BS EN 1307 Class 33 Heavy Commercial
Castor Chair Resistance	EN 985 ≥2500 cycles Pass 4.9 Suitable for intensive use
Dimensional Stability	ISO 2551 Pass
Thermal Resistance	ISO 8302 Suitable for underfloor heating
Slip Resistance	EN 13893 DIN 51130 R10 BS 7976-2:2002 +A1:2013 36+

Flame Properties

Fire rating	EN 13501-1 Bfl S1
Critical Radiant Flux	ASTM E 648 Class 1
Flammability	IMO FTPC Part 5 Low flame spread
Smoke Density	ASTM E 662 ≤450

Colour Fastness Properties

Light	ISO 105 B02 7-8
-------	-----------------

Acoustical Impact Noise Reduction

Impact sound insulation	EN ISO 10140 15dB
Airbourne sound absorption	EN ISO 354 0.05aw

Electrostatic Properties

Static Electricity	ISO 6356 Pass
--------------------	---------------

Recommended Adhesives

F Ball and Co

Permanent Bond F44, F45, F49

Heavy duty / Wet areas F74, F73 PLUS, F81, F84

www.f-ball.co.uk

General

Recommended maintenance

Can be swept, vacuumed and washed with a neutral cleaning agent. For heavier dirt, wet wash with a firm plastic bristle brush to lift dirt, then wipe over with an absorbent cloth.

Under Floor Heating

Suitable for use with underfloor heating

Laying Instructions (Rolls)

Must adhere fully to a smooth, solid, dry, clean and even ply or screed sub-floor, using an approved adhesive.

See website for full fitting instructions

For samples call 01548 434 998 or visit www.unnaturalflooring.com