
Product Specification

Unnatural flooring

Technical Specification

Product Definition.....	woven vinyl
Material.....	97% vinyl, 2% polyester, 1% glass fibre
Total Weight Tiles.....	4000gr/m ²
Total Weight Rolls.....	3000gr/m ²
Width of Rolls.....	200cm
Weight of standard Roll.....	340kg
Thickness Tiles.....	3.5mm
Thickness Rolls.....	3.0mm
Size Rolls.....	50m x 2m
Size Tiles.....	50cm x 50cm

Performance

Wear Classification.....	ISO/TR 10361.....	Heavy Contract
Castor Chair Test.....	EN425 pass >25,000 cycles	DIN 54324
Impact Noise Reduction.....	ISO717-2.....	19dB
DIN52210/4.....	19dB
NT ACOU.....	23dB
Dimensional Stability.....	EN434 <0.03%	
Slip Resistance.....	R10 DIN 51130	
BS 7976-2:2002+A1:2013	36+

Electrostatic Properties

Static Loading.....	ISO 3415 anti-static
Static Electricity.....	ISO 1815 anti-static

Flame Properties

Fire Standard.....	FRANCE Class M3
UK BS4790
EN13501-1 Class B s1
EN ISO 9239-1
EN ISO 11925-2
ASTME 662/DM 293/DM 373
Smoke Test.....	DIN 4102 B1
Flammability.....	IMO FTPC Part 5 Low flame spread

Product Specification

Unnatural flooring

Acoustical Impact Noise Reduction

.....EN ISO 140-8

Colour Fastness Properties

Light.....ISO 105 Bo2 >6

Recommended Adhesives

F Ball and Co.....Permanent bond F44, F45
.....Heavy duty/wet areas F74, F81, F84
.....www.f-ball.co.uk

UZIN Ltd.....High Traffic KR 430 NEW
.....Permanent Bond KE2000s / KE66 NEW
.....www.uzin.co.uk

General

Recommended Maintenance

Can be swept, vacuumed and washed with a neutral cleaning agent. For heavier dirt, wet wash with a firm plastic bristle brush to lift dirt, then wipe over with a cloth. See cleaning and care guide for full cleaning instructions.

Under Floor Heating.....Suitable for use with underfloor heating

Laying Instructions – Rolls.....Must adhere fully to a smooth, solid, dry, clean and even floor, using an approved adhesive.