



## Product Specification

### Unnatural Wood

#### Technical Specification

Product Definition	Luxury vinyl sheet	
Backing Material	PVC	
Total Thickness	EN ISO 24346	2.00mm
Wear Layer	EN ISO 24340	0.50mm
Wear Layer PUR treatment	Superguard®	
Total Weight	2358 g/m <sup>2</sup>	
Width of Roll	200cm and 400cm	
Length of Roll	25m	

#### Performance

Wear Classification	EN ISO 26986 Class 23 and 33
Castor Chair Test	EN ISO 4918 No damage to wear layer, no delamination.
Slip Resistance	EN 13893 DS DIN 51130 R10
Flammability	EN 13501 Bfl-S1
Thermal Resistance	EN 12667 0,0158m <sup>2</sup> .K/W
Heat Insulation	EN ISO 10456 0,25 w/(m.K)
Acoustic Insulation	EN ISO 717-2 8dB
Light Fastness	EN ISO 105-B02 ≥6
Dimensional Stability	EN ISO 23999 Norm: ≤0,40%
Residual Indentation	EN ISO 24343-1 Norm: ≤0,20mm
Underfloor Heating	EN 12524 Suitable
Stain Resistance	EN ISO 26987 Very good

#### Electrostatic Properties

Electrical Resistance	EN 1081 ≤10 <sup>8</sup> Ohm
Electrostatic Performance	EN 1815 <2kv

#### Recommended Adhesives

F.Ball and Co	Permanent bond F44, F46, F48+, F49 Heavy Duty / Wet Areas F74, F84 Vertical F49, F66
---------------	--