



## Product Specification

### Vermont Flooring

#### Technical Specification

Manufacturing Process:	Flat Woven
Pile Content:	Polypropylene
Backing:	Gel Backing
Total Weight:	1,700 gr/m <sup>2</sup>
Total Height:	Varies from 3.4mm – 5.1mm per weave – see website for details.
Width:	400cm

#### Performance

Wear Rating:	Class 23 Heavy domestic
Castor Chair Test:	EN 985 Residential use
Antistatic:	ISO 6356:2012
Thermal Resistance:	0.04m <sup>2</sup> K/W
Fire Resistance:	Dfl-s1

#### Suitability

Inside and Outside  
Underfloor Heating  
UV Stable

#### Recommended Adhesives

F.Ball & Co  
Styccobond F3  
Styccobond F60  
Styccobond F66

#### Colour Fastness Properties

Light	6
Water	4-5

[www.f-ball.co.uk](http://www.f-ball.co.uk)

#### General

Recommended Maintenance: Vacuum Daily.  
Do not over wet the areas.  
Professional cleaning is recommended periodically when the flooring becomes soiled.  
See website for full cleaning instructions.

#### Laying Instructions

The Vermont range can be fully adhered to the floor. If underlay is required, use a double stick method.  
See website for full fitting instructions.